

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 July 2005 (07.07.2005)

PCT

(10) International Publication Number
WO 2005/061261 A1

(51) International Patent Classification⁷: **B60K 17/10**,
F16H 39/02, B62M 19/00, 23/00

[SE/SE]; Snapphanevägen 6, Saleboda, S-370 34 Holmsjö
(SE).

(21) International Application Number:
PCT/SE2004/001782

(74) Agent: **KARLSSON**, Berne; P.O. Box 2078, S-137 02
Tungelsta (SE).

(22) International Filing Date: 2 December 2004 (02.12.2004)

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0303495-6 23 December 2003 (23.12.2003) SE

(71) Applicant (*for all designated States except US*): **ÖHLINS
RACING AB** [SE/SE]; Box 722, S-194 27 Upplands
Väsby (SE).


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **GUSTAVSSON, Leif**

[Continued on next page]

(54) Title: **DEVICE FOR USE IN A VEHICLE**



(57) Abstract: A vehicle (1) utilizes a hydrostatic transmission arrangement (10, 11, 12, 13). This transmits drive force (F) from at least one first wheel (2) to at least one second wheel (3). The arrangement comprises a hydrostatic pump, which can be driven with the first wheel, and a hydrostatic drive assembly, connected to the pump by a hydrostatic line system, for driving the second wheel (3). Additionally included are one or more members (19, 20) which wholly or partially bridge or disconnect the drive assembly. The said members are arranged to directly or indirectly detect or influence driving situations for the vehicle, for example the temperature in the hydrostatic medium, and, if change should occur, to cause or bring about the full or partial bridging or disconnection of the assembly. The functioning of the vehicle, which can thereby be made safer and developed with relatively less complicated means and can utilize, for example, conventional connecting hoses and associated connecting members, is thus improved. In an further embodiment the actuating members can be controlled by voice operating device(-s).



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*